

Elvanol™ as binder/water soluble film former

Binders

The unique properties of Elvanol™ polyvinyl alcohol make it a useful binder in many applications, like:

- Textile sizing
- Paper and paperboard sizing
- Pigmented coatings
- Cosmetic preparations
- Nonwoven binders
- Photosensitive coatings
- Ceramic binders
- Temporary binders in clay, gypsum, and cement
- Release coatings
- Leather treatment
- Chemical intermediate
- Moulded articles as gaskets, washers, diaphragms and tubing

Water soluble films

Films cast from waterborne solutions of Elvanol™ polyvinyl alcohol and plasticizer show particular characteristics: transparency, toughness, as well as tear and puncture resistance. Such films are used for hospital laundry bags that can be placed directly into the washing machine without the need for handling the contents.

Other Elvanol™ film applications

- water-soluble packaging
- release films
- vacuum bagging
- transfer printing
- water-soluble labels

Packaging

Elvanol™ grades can be used to produce water soluble film suitable for packaging preweighed quantities of materials, such as dyes, detergents, bluing, powdered bleaches, and fungicides. This allows their addition to aqueous systems without breaking the package or removing the contents, thereby saving time, limiting exposure to the contents and reducing material losses.

Other suggested applications in the packaging field include:

- container liners for oils, greases and paints.
- wrappers for protecting polished metals from gases such as oxygen and hydrogen sulphide.

Elvanol™ 71-30 is recommended for use in film manufacture where maximum strength and both, solvent resistance and resistance to cold water are desired. Elvanol™ grades 85-82 and 75-15 offer water solubility at intermediate temperature.



Adding value to your products – worldwide

KURARAY POVAL™, EXCEVAL™, ELVANOL™, and MOWIFLEX™ are the trademarks for polyvinyl alcohols (PVOH) made by Kuraray. Their key characteristics — outstanding film-forming properties and high binding strength — add real value to your products. Our polymers are water-soluble, highly reactive, crosslinkable and foamable. They have high pigment binding capacity, protective colloid characteristics and thickening effects. The physical and chemical properties of KURARAY POVAL™ make it ideal for a wide variety of applications, ranging from adhesives through paper and ceramics to packaging films. Many of our polymers are food contact-approved and thus suitable for food applications.

Kuraray produces its wide range of KURARAY POVAL™ grades in Japan, Singapore, Germany and the USA. Kuraray's global production and service network make us your partner of choice for innovative high-quality PVOH resins.



Kuraray Poval™

PLEASE CONTACT US
kuraray-poval.com

kuraray

HEADQUARTERS

Kuraray Co., Ltd.

Tokiwabashi Tower
2-6-4, Otemachi
Chiyoda-ku
Tokyo, Japan 100-0004

Kuraray America, Inc.

3700 Bay Area Blvd.,
Suite 680 Houston, TX 77058
United States of America

Kuraray Asia Pacific Pte., Ltd.

1 North Buona Vista Link
#12-10/11, Elementum
Singapore 139691

Kuraray Europe GmbH

Philipp-Reis-Str. 4
65795 Hattersheim am Main,
Germany

Kuraray China Co., Ltd.

Unit 2207, 2 Grand Gateway
3 Hongqiao Road, Xuhui District, Shanghai
200030, China

DISCLAIMER

KURARAY POVAL™, EXCEVAL™, ELVANOL™, and MOWIFLEX™ are the trademarks or registered trademarks of Kuraray or its affiliated companies. The information, recommendations, and details in this document are provided based on sufficient consideration to the best of Kuraray's knowledge. However, they are not intended to guarantee any characteristics beyond the product specifications. Customers should verify the suitability of our products for their intended use and compliance with relevant laws and regulations. Neither Kuraray nor any of its affiliated companies makes any warranty or responsibility for any errors, inaccuracies, or omissions in this document.